

Main Feature:

- Image CMOS Sensor
- IR Dome Camera
- 4MP Resolution @ (2560X1440P)
- 4mm HD Lens
- 2-Warm Light LED / up to 20-30Mtr.
- Mic Inbuilt & PoE Supported
- H.264 / H.265 / H.265+ Supported



2-Dual Light
IR array WL led's



Human
Target in true color



Connectivity
Network camera



High Definition
HD Recording



Microphone
Mic In-Built in Camera



MODEL

BT-IPC-ZMC4D2-A

| | |
|-------------------------|---|
| Image Sensor | 1/3 CMOS |
| Effective Pixels | 2560(H) * 1440(V) 4MP |
| Minimum Illumination | 0.05 Lux/F1.2(Color), 30IRE, 0lux/F1.2(B/W) |
| White Balance | Manual/Automatic |
| Gain Control (AGC) | Auto |
| Lens | 4mm |
| S/N Ratio | 50dB |
| Back Light Compensation | BLC/HLC/DWDR |
| Main Steam | PAL:2560x1440@12.5fps |
| Video Streaming | 2304 ^ * 1296 1920 ^ * 1080, 1280 ^ * 720, 1 - 30fps / s |
| Sub Steam | 704 ^ * 576, 640 ^ * 480, 640 ^ * 300, 352 ^ * 288, 1 - 30fps / s |
| Resolution | 4MP (2560 * 1440) |
| ICR | Auto (ICR)/Manual |
| Audio Input | 1 Channel |
| IR | IR Range of 20-30 Mtr. |
| OSD | OSD Supported |
| Operating Temperature | -30^ C sim+ 60 deg * C |
| Power Source | 12V DC |
| Power Consumption | 1.3W |
| Weatherproof Standard | IP66 |
| Protocol | ONVIF |
| Coding Format | H.265, H.264 |

